


# ARCUS S (Lens)

Fixed Recessed Downlight

## Product & Installation Details



## Product Details

### System Wattage

16W

### Lumen Output

1472lm

### Efficacy

92lm/W

### CCT [K]

3000 | 3500 | 4000 | 5700

### Beam Angle

30° / 36° / 50°

### Driver

450mA

## General Specification

### Product Preference

#### Environment

Indoor

#### Installation

Ceiling Recessed

### Construction & Materials

#### Bottom Ring

High Quality PC

#### Bottom Ring Finish

PC - White / Black

### Thermal Management

#### Heat Sink Material

Die Cast Aluminium

#### Cooling Technique

Passive Cooling

### LED Technology

#### LED Life Time @L70/B10

>50000 Hrs.

#### Colour Rendering (CRI)

CRI90 as Standard

### General Features

#### Operating Temperature

0°C-50°C

#### Ingress Protection (IP)

IP20

### Electrical System

#### Driven With

Constant Current Driver

#### Input Voltage

220V-240V/50-60Hz

#### Driver

Non-Integrated

### Controls

#### Standard

On / Off

#### Optional

Mains / Analog / Dali

Bluetooth

### Optical System

#### Beam Direction

Non-Adjustable

#### Tilt

No

#### Swivel

No

## Product Details:

| Product Name  | CCT | Beam Angle      | Finish        | Dimming Option  |
|---------------|-----|-----------------|---------------|-----------------|
| ARCUS S - 16W | CW  | 30° / 36° / 50° | White / Black | BLE/DALI/ANALOG |
|               | NW  | 30° / 36° / 50° | White / Black | BLE/DALI/ANALOG |
|               | WW  | 30° / 36° / 50° | White / Black | BLE/DALI/ANALOG |



\*Parameters may differ due to CCT or Driver current variation.

