


ARCUS M (Lens)

Fixed Recessed Downlight

Product & Installation Details



Product Details

System Wattage

25W

Lumen Output

2625lm

Efficacy

105lm/W

CCT [K]

3000 | 3500 | 4000 | 5700

Beam Angle

22°/ 30°/ 36°/ 60°

Driver

600mA

General Specification

Product Preference

Environment

Indoor

Installation

Ceiling Recessed

Construction & Materials

Bottom Ring

High Quality PC

Bottom Ring Finish

PC - White / Black

Thermal Management

Heat Sink Material

Die Cast Aluminium

Cooling Technique

Passive Cooling

LED Technology

LED Life Time @L70/B10

>50000 Hrs.

Colour Rendering (CRI)

CRI90 as Standard

General Features

Operating Temperature

0°C-50°C

Ingress Protection (IP)

IP20

Electrical System

Driven With

Constant Current Driver

Input Voltage

220V-240V/50-60Hz

Driver

Non-Integrated

Controls

Standard

On / Off

Optional

Mains / Analog / Dali

Bluetooth

Optical System

Beam Direction

Non-Adjustable

Tilt

No

Swivel

No

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
ARCUS M - 25W	CW	22°/ 30°/ 36°/ 60°	White / Black	BLE/DALI/ANALOG
	NW	22°/ 30°/ 36°/ 60°	White / Black	BLE/DALI/ANALOG
	WW	22°/ 30°/ 36°/ 60°	White / Black	BLE/DALI/ANALOG



*Parameters may differ due to CCT or Driver current variation.

