


AVIO NX SQ 1X

Product & Installation Details



Cut-Out: 140 x 140mm
*All dimensions are in mm.

Product Details

System Wattage

25W

Lumen Output

2600lm

Efficacy

104lm/W

CCT [K]

3000 | 4000 | 5700 | 6500

Beam Angle

24° / 40° / 60°

Driver

600mA

General Specification

Product Preference

Lighting Type

Adjustable Spotlight

Environment

Indoor

Installation

Recessed Mounting

Construction & Materials

Housing

Die Cast Aluminium

Body Finish

Powder Coating - White / Black

Thermal Management

Heat Sink Material

Die Cast Aluminium

Cooling Technique

Passive Cooling

LED Technology

LED Life Time @L70/B10

>50000 Hrs.

Colour Rendering (CRI)

CRI80 as Standard

General Features

Operating Temperature

0°C-50°C

Ingress Protection (IP)

IP20

Electrical System

Driven With

Constant Current Driver

Input Voltage

220V-240V/50-60Hz

Driver

Non - Integrated

Controls

Standard

On / Off

Optional

Mains / Analog / Dali
Bluetooth / Phase Cut

Optical System

Beam Direction

Adjustable

Tilt

Yes

Swivel

Yes

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
AVIO NX SQ. 1X 25W	CW	24° / 40° / 60°	White / Black	Not Available
	NW	24° / 40° / 60°	White / Black	Not Available
	WW	24° / 40° / 60°	White / Black	Not Available



*Parameters may differ due to CCT or Driver current variation.

