


CIRCA

Product & Installation Details



Product Details

System Wattage

30W

Lumen Output

3000lm

Efficacy

100lm/W

CCT [K]

2700 / 3000 / 4000 / 6500

Beam Angle

Diffused

Driver

300mA

General Specification

Product Preference

Lighting Type
Surface Downlight

Environment
Indoor / Outdoor

Installation
Surface Mounting

Construction & Materials

Housing
Die Cast Aluminium

Body Finish
Powder Coating - White / Black

Thermal Management

Heat Sink Material
Die Cast Aluminium

Cooling Technique
Passive Cooling

LED Technology

LED Life Time @L70/B10
>50000 Hrs.

Colour Rendering (CRI)
CRI80 as Standard

General Features

Operating Temperature
0°C-50°C

Ingress Protection (IP)
IP65

Driver
Integrated

Electrical System

Driven With
Constant Current Driver

Input Voltage
220V-240V/50-60Hz

Output Voltage
27~40V

Controls

Standard
On / Off

Optional
Mains / Analog / Dali / BLE

P.F. / THD
>0.8 / ≤15%

Optical System

Beam Direction
Fix

Tilt
Fix

Swivel
No

Product Details:

Product Name	CCT	Light Spreading Angle	Finish	Dimming Option
CIRCA - 30W	CW	Diffused	Black / White	BLE/DALI/ANALOG
	NW	Diffused	Black / White	BLE/DALI/ANALOG
	WW	Diffused	Black / White	BLE/DALI/ANALOG



*Parameters may differ due to CCT or Driver current variation.

