


COMET

Product & Installation Details



All dimensions are in mm.*

Product Details

System Wattage

30W

Lumen Output

3900lm

Efficacy

130lm/W

CCT [K]

2700 | 3000 | 4000 | 6000

Beam Angle

15°, 24°, 36°, 45°, 60°

Driver

700mA / 750mA

General Specification

Product Preference

Environment

Indoor

Installation

Track Mounted

Construction & Materials

Housing

Die Cast Aluminium

Body Finish

Powder Coating - Black / White

Thermal Management

Heat Sink Material

Die Cast Aluminium

Cooling Technique

Passive Cooling

LED Technology

LED Life Time @L70/B10

>50000 Hrs.

Colour Rendering (CRI)

CRI90 as Standard

General Features

Operating Temperature

0°C-50°C

Ingress Protection (IP)

IP20

Electrical System

Driven With

Constant Current Driver

Input Voltage

220V-240V/50-60Hz

Driver

Non-Integrated

Controls

Standard

On / Off

Optional

Mains / Analog / Dali

Optical System

Beam Direction

Adjustable

Tilt

Yes

Swivel

Yes

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
COMET - 30W	CW	15°/ 24°/36°/45°/60°	White / Black	DALI/ANALOG
	NW	15°/ 24°/36°/45°/60°	White / Black	DALI/ANALOG
	WW	15°/ 24°/36°/45°/60°	White / Black	DALI/ANALOG



*Parameters may differ due to CCT or Driver current variation.

