


Dot

Product & Installation Details



Product Details

System Wattage

15W

Lumen Output

1500lm

Efficacy

100lm/W

CCT [K]

3000K / 4000K / 5700K / 6500K

Beam Angle

24° / 36°

Driver

350mA

General Specification

Product Preference

Environment

Indoor

Installation

Ceiling Recessed

Construction & Materials

Housing

Die Cast Aluminium

Body Finish

Powder Coating

Black / White / Custom

Thermal Management

Heat Sink Material

Die Cast Aluminium

Cooling Technique

Passive Cooling

LED Technology

LED Life Time @L70/B10

>50000 Hrs.

Colour Rendering (CRI)

CRI80 as Standard

General Features

Operating Temperature

0°C-50°C

Ingress Protection (IP)

IP20

Electrical System

Driven With

Constant Current Driver

Input Voltage

220V-240V/50-60Hz

Driver

Non-Integrated

Controls

Standard

On / Off

Optional

Mains / Analog / Dali

Bluetooth

Optical System

Beam Direction

Fixed

Tilt


No

Swivel

No

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
DOT - 15W	CW	24° / 36°	Black / White	BLE/DALI/ANALOG
	NW	24° / 36°	Black / White	BLE/DALI/ANALOG
	WW	24° / 36°	Black / White	BLE/DALI/ANALOG



*Parameters may differ due to CCT or Driver current variation.

