


DART

Product & Installation Details



Product Details

System Wattage
30W

Lumen Output
3000lm

Efficacy
100lm/W

CCT [K]
3000 | 4000 | 6500

Beam Angle
24°/ 36°/ 60°

Driver
800mA

General Specification

Product Preference

Environment
Indoor

Installation
Ceiling Recessed

Construction & Materials

Housing
Die Cast Aluminium

Body Finish
Powder Coating - White

Thermal Management

Heat Sink Material
Die Cast Aluminium

Cooling Technique
Passive Cooling

LED Technology

LED Life Time @L70/B10
>50000 Hrs.

Colour Rendering (CRI)
CRI80 as Standard

General Features

Operating Temperature
0°C-50°C

Ingress Protection (IP)
IP20

Electrical System

Driven With
Constant Current Driver

Input Voltage
220V-240V/50-60Hz

Driver
Non-Integrated

Controls

Standard
On / Off

Optional
Mains / Analog / Dali
Bluetooth

Optical System

Beam Direction
Non-Adjustable

Tilt
No

Swivel
No

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
DART - 35W	CW	24°/ 36°/ 60°	White / Black	BLE/DALI/ANALOG
	NW	24°/ 36°/ 60°	White / Black	BLE/DALI/ANALOG
	WW	24°/ 36°/ 60°	White / Black	BLE/DALI/ANALOG



*Parameters may differ due to CCT or Driver current variation.