


GLINT

LED MR16 Module

Product & Installation Details



Product Details

System Wattage

15W

Lumen Output

1500lm

Efficacy

100lm/W

CCT [K]

2700 | 3000 | 4000 | 6000

Beam Angle

15°, 24°, 36°

Driver

350mA

General Specification

Product Preference

Environment

Indoor

Installation

Recessed Mounted

Construction & Materials

Housing

Die Cast Aluminium

Body Finish

Powder Coating - Black / White

Thermal Management

Heat Sink Material

Die Cast Aluminium

Cooling Technique

Passive Cooling

LED Technology

LED Life Time @L70/B10

>50000 Hrs.

Colour Rendering (CRI)

CRI80 as Standard

General Features

Operating Temperature

0°C-50°C

Ingress Protection (IP)

IP20

Electrical System

Driven With

Constant Current Driver

Input Voltage

220V-240V/50-60Hz

Driver

Non - Integrated

Controls

Standard

On / Off

Optional

Mains / Analog / Dali

BLE

Optical System

Beam Direction

Fixed

Tilt

No

Swivel

No

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
GLINT - 15W	CW	15°/24°/36°	White / Black	DALI/ANALOG/BLE
	NW	15°/24°/36°	White / Black	DALI/ANALOG/BLE
	WW	15°/24°/36°	White / Black	DALI/ANALOG/BLE



*Parameters may differ due to CCT or Driver current variation.

