


MGT23-PDT D

Magnetic Decorative Pendant

Product & Installation Details



Product Details

System Wattage
10W

Lumen Output
1000lm

Efficacy
100lm/W

CCT [K]
3000 | 4000 | 6000

Beam Angle
24°

Driver
48VDC

General Specification

Product Preference

Environment
Indoor

Installation
Track Mounted

Construction & Materials

Housing
Die Cast Aluminium

Body Finish
Powder Coating - Black / White

Thermal Management

Heat Sink Material
Die Cast Aluminium

Cooling Technique
Passive Cooling

LED Technology

LED Life Time @L70/B10
>50000 Hrs.

Colour Rendering (CRI)
CRI90

General Features

Operating Temperature
0°C-50°C

Ingress Protection (IP)
IP20

Electrical System

Driven With
Constant Voltage Driver

Input Voltage
220V-240V/50-60Hz

Driver
Integrated

Controls

Standard
On / Off

Optional
Mains / Analog / Dali
Bluetooth

Optical System

Beam Direction
NA

Tilt
NA

Swivel
NA

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
MGT23-PDT D - 10W	CW	24°	White / Black	BLE/DALI/ANALOG
	NW	24°	White / Black	BLE/DALI/ANALOG
	WW	24°	White / Black	BLE/DALI/ANALOG



*Parameters may differ due to CCT or Driver current variation.

Focus Lighting & Fixtures Ltd.

1007-1010 - Corporate Avenue,
Sonawala Cross Lane, Near Udyog Bhawan
Goregaon - (E) - 400063



www.trix.co.in

*Please print this spec sheet only if necessary. Go Green.