


# VERVE S Round

## Product & Installation Details



## Product Details

**System Wattage**  
24W

**Lumen Output**  
2208lm

**Efficacy**  
92lm/W

**CCT [K]**  
3000 | 4000 | 6000

**Beam Angle**  
120°

**Driver**  
650mA

## General Specification

### Product Preference

**Environment**  
Indoor

**Installation**  
Ceiling Recessed

### Construction & Materials

**Housing**  
Die Cast Aluminium

**Body Color**  
White / Black Heat Sink

### Thermal Management

**Heat Sink Material**  
Die Cast Aluminium

**Cooling Technique**  
Passive Cooling

### LED Technology

**LED Life Time @L70/B10**  
>50000 Hrs.

**Colour Rendering (CRI)**  
CRI80 as Standard

### General Features

**Operating Temperature**  
0°C-50°C

**Ingress Protection (IP)**  
IP20

### Electrical System

**Driven With**  
Constant Current Driver

**Input Voltage**  
220V-240V/50-60Hz

**Driver**  
Non-Integrated

### Controls

**Standard**  
On / Off

**Optional**  
Mains / Analog / Dali  
Bluetooth / Phase Cut

### Optical System

**Beam Direction**  
Fixed

**Tilt**  
No

**Swivel**  
No

## Product Details:

| Product Name     | CCT | Beam Angle | Finish | Dimming Option    |
|------------------|-----|------------|--------|-------------------|
| VERVE S RD - 24W | CW  | 120°       | White  | BLE/ DALI/ ANALOG |
|                  | NW  | 120°       | White  | BLE/ DALI/ ANALOG |
|                  | WW  | 120°       | White  | BLE/ DALI/ ANALOG |



\*Parameters may differ due to CCT or Driver current variation.

