



ZEUS - 1X

Product & Installation Details



Product Details

System Wattage
5W

Lumen Output
450lm

Efficacy
90lm/W

CCT [K]
3000 | 4000 | 6500

Beam Angle
30°

Driver
150mA

General Specification

Product Preference

Environment
Indoor

Installation
Ceiling Recessed

Construction & Materials

Housing
Die Cast Aluminium

Body Finish
Powder Coating - Black / White

Thermal Management

Heat Sink Material
Die Cast Aluminium

Cooling Technique
Passive Cooling

LED Technology

LED Life Time @L70/B10
>50000 Hrs.

Colour Rendering (CRI)
CRI80 as Standard

General Features

Operating Temperature
0°C-50°C

Ingress Protection (IP)
IP20

Electrical System

Driven With
Constant Current Driver

Input Voltage
220V-240V/50-60Hz

Driver
Non-Integrated

Controls

Standard
On / Off

Optional
Mains / Analog / Dali
Bluetooth

Optical System


Beam Direction
Non-Adjustable

Tilt
No

Swivel
No

Product Details:

Product Name	CCT	Beam Angle	Finish	Dimming Option
ZEUS 1X - 5W	CW	30°	White / Black	Not Available
	NW	30°	White / Black	Not Available
	WW	30°	White / Black	Not Available



*Parameters may differ due to CCT or Driver current variation.

